


## Super Flat Surface 90x90 No Dimmable


Designed by FLOS Architectural, 2018



Surface mounted general lighting LED luminaire. Power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	55
Source flux (lm)	5651.36
System flux (lm)	4998

### Physical

Colour	White
Trim	No
Orientation	Fixed
Net weight (kg)	9.90
IP internal	20
IP external	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ LDT](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	104
Beam angle C90-270 (°)	107

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	35.00
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Total consumption of the system: 55W. Light source: max. 7660 lm. Luminous efficiency of luminaire: max. 151 lm/W.