

PALMA

Design by Antoni Arola.

Reference

3726.

Application

Hanging lamps

Installation type

Surface

Description

Pendant lamp. The effect of floating through its multiple configurations thanks to the almost imperceptible suspension and unique cable system and the hoops that wrap the spheres.

Diffuser

Mat opal triplex blown-glass diffuser

Materials

Profile: Aluminum

Diffuser: Blown-glass

Finish




3726-18 Matt graphite lacquer (ADAPTA RF 9913 WX)



3726-93 Matt white lacquer (RAL 9016)

Sketch



Electrical characteristics



Led 2700K CRI >90 1736 lm 93 lm/W

Fixture: 1153.01 lm 49.57 lm/W

Driver included: CC - Constant Current 500 mA 110-240V 50/60Hz

Electronic dimming 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional DALI

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0725 m³ /

Gross weight 6.4 kg. / Net weight 4.4 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1153.01 lm

Maximum value : 67.81 cd/klm

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

