



WEVER & DUCRÉ  
LIGHTING

# MILES 12.0

317978W3

Project

Type

Notities

Kwantiteit

Datum

## ALGEMEEN

Wand

Opbouw

Signaalwit

IP20

Interieur

2130 lm

RAL 9003<sup>a</sup>

## LED

2700 K

CRI  $\geq$  90

L80 B50 / 60000h

3-step binning

## FYSISCH

Lengte 1200 mm

Width 30 mm

Height 80 mm

2.62 kg

## ELEKTRISCH

phase-cut dim



220 - 240 V

Totaal aangesloten vermogen 38 W


Klasse I

Veiligheidsafstand 0.3 m

<sup>a</sup> Color may deviate slightly due to production conditions.



## LICHTVERDELING





WEVER & DUCRÉ  
LIGHTING

# MILES 12.0

317978W3

## Onderhoudsfactoren

Bedrijfstijd [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.89
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Onderhoudsfactor ruimte
MF	Onderhoudsfactor	LLMF	Lumenbehoudfactor lichtbron
LMF <sup>a</sup>	Behoudfactor armatuur	LSF	Overlevingsfactor lichtbron

<sup>a</sup> Volgens "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. De waarden moeten bepaald worden door de planningverantwoordelijke.