



WEVER & DUCRÉ  
LIGHTING

# TAPE 1.0

722174W5

Project
Type
Notes
Quantity
Date

## GENERAL

Wall  
 Surface  
 Signal White  
 IP65  
 Exterior  
 420 lm  
 RAL 9003<sup>a</sup>

## LED

3000 K  
 CRI 90  
 L95 / 50000 h  
 3-step binning

## OPTICAL

Wide Flood

## PHYSICAL

Length 180 mm  
 Width 180 mm  
 Height 60 mm  
 0.73 kg


## ELECTRICAL

phase-cut dim  
 220 - 240 V  
 Total connected power 8 W  
 PC1  
 Safety distance 0.3 m


<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



IP65 <0,3>



## LIGHT DISTRIBUTION



[722174W5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.  
 © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



**WEVER & DUCRÉ**  
LIGHTING

# TAPE

## 1.0

722174W5

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.98	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.