

# FLOS

09.2110.40C White

## Fort Knox Wall LED Dimmable 1-10V

Designed by Philippe Starck, 2018




LED - Power LED - 30.7W - 3036lm - 3000K - CRI> 90 - Beam° 29

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Wall surface
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Lamp category	LED
Icos	No
Number of heads	1
Power (W)	30.7
System power (W)	35
Source flux (lm)	3900
System flux (lm)	3036

### Physical

Colour	White
Trim	No
Orientation	Fixed
Length (mm)	200
Net weight (kg)	1.4
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



## Schematic light drawing



## Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50 50.000h
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	86

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 1-10V

## Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional